

Enhanced photoluminescence in plasmonic resonant nanocavities

K. Munechika, T. Bond, M. Bora, A. SP. Chang, E. M. Behymer, D. A. Dehlinger, J. A. Britten, C. C. Larson, H. T. Nguyen

November 27, 2012

Materials Research Society Boston, MA, United States November 25, 2012 through November 30, 2012

Disclaimer

This document was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor Lawrence Livermore National Security, LLC, nor any of their employees makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or Lawrence Livermore National Security, LLC. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or Lawrence Livermore National Security, LLC, and shall not be used for advertising or product endorsement purposes.


Enhanced Photoluminescence in Plasmonic Resonant Nanocavities

K. Munechika, M. Bora, E. M. Behymer, D. Dehlinger, J. Britten, C. C. Larson, A. SP Chang, H. T. Nguyen, and T. Bond Lawrence Livermore National Laboratory








Plasmon resonant cavities




Plasmon coupling with incident radiation








Tuning the plasmon resonance



Enhanced dipole absorbance




The field enhancement decreases with absorbance

Dissipated energy in the cavity has a maximum with respect to

$$\alpha_{abs} = \frac{2\pi\varepsilon_{im}}{\lambda_0}$$


 ϵ_{im}


Enhanced dipole emission




Point dipole emission profile from within the resonant cavity follows the electric field pattern of the resonant modes in both position and frequency

Experimental Setup







Tuning the plasmon resonance frequency with solvents





➤ Reflectance spectra of Ag nanocavities were measured while immersed in solvents with different refractive indices (methanol *n*= 1.328 and DMSO *n*=1.479).


Sample Scheme











Summary and Future Plans

- 3D arrays of nanowires show tunable plasmon resonances in the visible region (height & gap control)
- Plasmon resonance frequency of nanocavities can be tuned
 100 nm by changing the RI of solvents
- Observed reduced (~ 20X) photoluminescence lifetime of Nile Blue dyes on the plasmonic nanocavities
- Fraction of shorter lifetimes (compared to pristine dye photoluminescence lifetime) is maximized when the plasmon resonance frequency is off-resonance from the emission maxima
- Future work include parametric study and systematic control of plasmonic resonances with respect to dye excitation/emission frequency

Acknowledgements

Lawrence Livermore National Laboratory Engineering Directorate Materials Engineering Division

Dr. Ted Lawrence

Dr. Mihail Bora

Dr. Sonny Ly

Dr. Elaine M. Behymer

Dr. Dietrich A. Dehlinger

Dr. Jerald A. Britten

Dr. Cindy C. Larson

Dr. Allan SP Chang

Dr. Hoang T. Nguyen

Dr. Tiziana C. Bond

Prepared by LLNL under Contract DE-AC52-07NA27344

Thank you for your attention!